





### **KEY FEATURES**

- ▶ Smart IR II (Combining the High Beam and Low Beam to adjust IR intensity to fit different lighting conditions.)
- ▶ P2P (Remotely access the camera using 5G network via P2P with hassle-free setup and easy connection.)
- ► HLC (High Light Compensation. Improving image visibility under strong light sources.)
- Defog (Defog technology. Restoring clear images in hazy and foggy weather.)
- Integrated Cable Management (Combining the power interface, PoE port, and other interfaces in the base neatly.)
- ▶ 1TB (Supporting ultra-large external microSD/SDHC/SDXC card storage up to 1TB.)
- ▶ Smart Stream (Bandwidth, storage and bit rate are saved with Smart Stream On, eg, H.265+ saves 70%~80% bandwidth that of H.264)

#### **5G Technology**

Camera responsiveness and real-time monitoring can be greatly enhanced by the larger bandwidth and lower latency of 5G networks, not to mention a leap in ultra-high-definition video or images. The 5G camera comes with its 5G cellular module, which is fit for some scenarios where wiring is inconvenient, and its higher performance of mobility, security and coverage also bring new opportunities for the industry.



#### 0.005Lux Ultra Low-light

The starlight camera is able to deliver high detailed color images even in low light environment reaching 0.005Lux(Color) or 0Lux(B/W), and near infrared light environments without any supplementary lighting.



### Al Video Analytics

- 9 intelligent VCA modes powered by AI engine, which can intelligently filter objects to focus on human and vehicle detection.
- Object Counting technology provides high accuracy and real-time data based on Al algorithm with statistic reports.
- Face Detection function detects human faces in the monitoring scene and captures the snapshots, which greatly enhances the monitoring efficiency.



### Easy Deployment and Compact Structure

5G antenna is built outside the camera and the 5G module is directly merged inside the camera. By inserting the SIM card, you can monitor in places where network wiring is not convenient. Versatile interface and integrated junction box ensure installation neat and tidy.



	9.

Camera	Model	MS-C2966-RF(I)GPE (2MP)	MS-C8266-F(I)GPE (4K)	
	Image Sensor	1/2.8" Progressive Scan CMOS	1/1.8" Progressive Scan CMOS	
	Min. Illumination	Color: 0.005Lux@F1.4 B/W: 0Lux with IR on	Color: 0.009Lux@F1.4 B/W: 0Lux with IR on	
	WDR	140dB Super WDR	120dB Super WDR	
	Shutter Time	1/100000s~1s		
	IR Distance	Up to 65m(2.7~13.5mm) Up to 100m(7~22mm)	Up to 65m	
	Day/Night Mode	Day/Night/Auto/Customize/Schedule		
	S/N	>55dB		
	Lens	Motorized 2.7~13.5mm/7~22mm@F1.4 P-Iris(Optional)	Motorized 3.6~10mm@F1.4 P-Iris(Optional)	
	Field of View	H113°~H33°/D130°~D38°/V60°~V18° (2.7~13.5mm) H45°~H17°/D53°~D20°/V25°~V9° (7~22mm)	H116°~H48°/D134°~D55°/V65°~V27°	
Lens	Mount	Ф14		
	Focus Control	Auto/Manual		
	Iris Control (Optional for I Series)	Auto/Manual		
	Max.Image Resolution	1920x1080	3840x2160	
Video	Primary Stream	60Hz: 60fps@(1920x1080, 1280x960, 1280x720, 704x576) 50Hz: 50fps@(1920x1080, 1280x960, 1280x720, 704x576)	60Hz: 30fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 704x576) 50Hz: 25fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 704x576)	
	Secondary Stream	60Hz: 60fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180) 50Hz: 50fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)	60Hz: 30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180) 50Hz: 25fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)	
	Tertiary Stream	60Hz: 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180) 50Hz: 25fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180)		
	Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG		
	Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)		
	Privacy Masking	Up to 8 Areas (Mask Area and Mosaic Area are optional)		
	ROI	Up to 8 areas		
	Image Setting	Brightness/Contrast/Saturation/Sharpness		



	9)

Ethernet 1*RJ45 10M/100M Ethernet Port		
Interface Audio I/O 1/1		
Alarm I/O 1/1		
Wireless Communication Support 5G/4G/3G		
	n1/n2/n3/n5/n7/n8/n12/n13/n14/n18/n20/n25/n26/n28/n29/n30/n38/n40/n41/n48/n66	
5G NR /n70/n71/n75/n76/n77/n78/n79	0,1141,1140,1100	
B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B18/B19/B20		
Frequency LTE-FDD /B25/B26/B28/B29/B30/B32/B66/B71		
Mobile Bands LTE-TDD B34/B38/B39/B40/B41/B42/B48		
Communication LAA B46		
Parameter WCDMA B1/B2/B4/B5/B8/B19		
Wireless SA DL 2.4Gbps; UL 900Mbps		
Transmission NSA DL 3.4Gbps; UL 550Mbps		
Speed LTE DL 1.6Gbps; UL 200Mbps		
SIM Card Nano SIM	Nano SIM	
Network Storage NAS(Support NFS, SMB/CIFS	NAS(Support NFS, SMB/CIFS	
Network  IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, F	TP, NTP, SMTP, SNMP,	
UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL, TL	S 1.2	
Audio Compression G.711/AAC/G.722/G.726	G.711/AAC/G.722/G.726	
Audio Sampling Rate 8/16/32/44.1/48KHz	8/16/32/44.1/48KHz	
Audio Bit Rate 16~256kbps	16~256kbps	
Two-way Audio Support		
Intrusion Detection, Region Entrance, Region Exiting, Advanced Motion Detection Video Analysis	, Tamper Detection,	
Line Crossing, Loitering, Object Left, Object Removed		
Intelligent  Detect and capture faces, get real-time snapshots;  The attribute include Ann Courter Classes Made and Courter Classes Made and Courter Classes and Court		
Analytics Face Detection The attributes include Age, Gender, Glasses, Mask and Cap. Support Faces Privacy Mode, the detected faces in the face detection area will be	mosaic automatically	
Object Counting&  Count the number of objects crossing the line, optionally human and	-	
Report Support regional people counting for up to 4 detection areas		
Storage Support microSD/SDHC/SDXC Card Local Storage, up to 1TB		
Heat Map, BLC, HLC, 2D DNR, 3D DNR, Advanced Function		
Detog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Debi	ur, Watermark	
System SIP/VoIP Support Yes, Voice & Video-over-IP	Yes, Voice & Video-over-IP	
Event Trigger Motion Detection, Network Disconnection, External Input, Audio Ala	Motion Detection, Network Disconnection, External Input, Audio Alarm, etc.	
Event Action FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP	Notification, etc.	
System Compatibility ONVIF Profile G & M & S & T, API		








General	Working Temperature	-40°C~60°C	
	Working Humidity	0~90%(Non-condensing)	
	Power Supply	PoE (802.3at) / DC 12V $\pm$ 10%	
	Power Consumption	9W MAX 14W MAX (With IR on)	10W MAX 16W MAX (With IR on)
	Surge Protection	4KV	
	Weather Proof	Up to IP67-rated for Weather-resistant Performance (Only for camera body)	
	Weight	1650g	
	Dimensions	320mmX134mmX126mm 320mmX134mmX208mm (With Antennas)	
	Warranty	3/5 Years	





## Structure Diagrams
















Units: mm

#### A62 Junction Box(Default)

Weight: 510g

Dimensions: 134\*126\*40mm



#### A02 V2 Pole Mount

Weight: 1kg

Dimensions:180\*136\*46mm





#### **A03 External Corner Bracket**

Weight: 900g

Dimensions: 170\*152.5\*76.3mm



